

ASH SERIES

"Everyone is relaxed when they are at my home."



ASH series High wall

Aircool © is a big name in airconditioning systems. Because of their slim design and easy installation Aircool airconditioners are especially suitable for residential use. The capacity of the units are adapted to their use, therefore they run silently and energy efficient. The ASH models are available from 2,1 up to 7,0 kW.



ASH High wall



Strenghts of the ASH airconditioners:

- Wireless remote control with 24-hours timer
- Auto-swing function
- Vitamin C filter (optional)
- Power blackout auto restart function
- Self diagnostic function and error report



Wireless remote



Indoor unit



Compact outdoor unit

Model	ASH	25HMF1	35HMF1	50HMF1	71HMF1
Specifications set					
Cooling capacity	kW	2,6	3,5	5,0	7,0
Heating capacity	kW	2,8	4,1	5,3	7,6
Voltage	V/pH/Hz	230/1/50	230/1/50	230/1/50	230/1/50
E.E.R.		3,21	3,21	3,01	2,81
Energylabel cooling		A	A	B	C
C.O.P.		3,61	3,61	3,41	3,21
Energylabel heating		A	A	B	C
Specifications indoor unit					
Airvolume low/high	m ³ /h	350/470	400/560	470/995	920/1150
Sound Level low/high	dB(A)	27/34	29/40	30/41	38/47
Drainhose connection	mm	Ø16	Ø16	Ø16	Ø16
Height	mm	290	290	292	320
Width	mm	845	845	995	1080
Depth	mm	165	165	200	225
Weight	kg	9,0	9,0	11,5	14,0
Specifications outdoor unit					
Airvolume	m ³ /h	1650	1900	2200	2700
Sound Level	dB(A)	54	54	57	62
Height	mm	535	540	590	695
Width	mm	700	780	760	845
Depth	mm	235	250	285	335
Weight	kg	24,5	32,5	38,5	52,0

ASH High wall Inverter



Strenghts of the ASH airconditioners:

- Wireless remote control with 24-hours timer
- Auto-swing function
- Vitamin C filter (optional)
- Power blackout auto restart function
- Self diagnostic function and error report



Wireless remote



Indoor unit



Compact outdoor unit

Model	ASH	25HMMI	35HMMI	50HMMI
Specifications set				
Cooling capacity	kW	2,6	3,5	5,0
Cooling range limitations	kW	0,9~3,4	1,1~4,3	1,5~6,4
Heating capacity	kW	2,9	3,8	5,3
Heating range limitations	kW	1,0~3,7	1,2~4,5	1,9~6,4
Voltage	V/pH/Hz	230/1/50	230/1/50	230/1/50
E.E.R.		3,81	3,41	3,21
Energylabel cooling		A	A	A
C.O.P.		4,21	3,81	3,61
Energylabel heating		A	A	A
Specifications indoor unit				
Airvolume low/high	m ³ /h	400/550	440/580	530/720
Sound Level low/high	dB(A)	26/38	37/39	28/40
Height	mm	290	290	292
Width	mm	845	845	995
Depth	mm	165	165	200
Weight	kg	9,0	9,0	11,5
Specifications outdoor unit				
Airvolume	m ³ /h	2000	2000	2000
Sound Level	dB(A)	54	54	56
Height	mm	590	590	590
Width	mm	760	760	760
Depth	mm	285	285	285
Weight	kg	38,5	39,0	39,5

Certified installer



Aircool® airconditioning systems meet the highest technical standards. For a solid advice you can contact a certified installer in your neighborhood. Those certified installers are skilled professionals who are pleased to meet your requirements.

Your consultant/installer.


COOL SERVIS s.r.o., Čsl. armády 2243, 39003 Tábor 3

telefon:	www.coolservis.cz	GSM:
381 231 000	www.klimatizace.org	608 231 000
381 231 555	www.t-cerpadla.cz	Skype:
381 231 888	E-mail: info@coolservis.cz	coolservis

